

MULCHER



IDEAL FOR FOREST CARE, PARKS AND GARDEN MAINTENANCE

Heavy operations such as bushwood clearance or land maintenance are perfect applications for the Cangini Mulcher/flail.

This attachment is rugged and durable, thanks above all to its reinforced casing with double bottom, which provides outstanding resistance to impacts and torsional forces. The shielded bearings of the rollers protect them from collisions with material in the mulching area. Use this renowned attachment on excavators from 1.5T to 6.5T.



www.augertorque.com.au

CALL 13 22 12 EMAIL sales@augertorque.com.au



Features

- Shaft equipped with either blade or hammer set up
- Adjustable height support roller
- High quality motor and hoses
- Self levelling frontal plane
- Highly resistant with an integrated valve unit as standard

Specifications

Applications

- Ground clearance
- Woodland pathway creation and maintenance
- Clear and maintain vegetation
- Tree and hedge trimming
- Mulch trees and hedges down to ground level
- Cut shrubs up to 10cm in diameter

Models		TC1-80	TC2-80	TC2-100
Carrier weight		1.5 - 3.5T	3.5 - 6.5T	3.5 - 6.5T
Drum width	mm	800	800	1000
'A'	(inch)	(31)	(31)	(39)
Overall width	mm	1000	980	1180
'B'	(inch)	(39)	(39)	(46)
Depth	mm	640	810	810
'C'	(inch)	(25)	(32)	(32)
Height	mm	461	530	530
'D'	(inch)	(18)	(21)	(21)
Weight	kg	115	245	270
	(lbs)	(254)	(540)	(595)
Flow rate	lpm	18 - 90	28 - 90	28 - 90
	(gpm)	(5 - 24)	(7 - 24)	(7 - 24)
Pressure	bar	250	250	250
bar (psi)	(psi)	(3626)	(3626)	(3626)
Cutting diameter with hammer	mm (inch)	20 - 30 (0.8 - 1.2)	40 - 60 (1.6 - 2.4)	40 - 60 (1.6 - 2.4)



Part of the Auger Torque landscaping range STUMP PLANERS | LOG SPLITTERS | MULCHERS | HEDGE TRIMMERS | SWEEPER BROOMS

www.augertorque.com.au

CALL 13 22 12 | EMAIL sales@augertorque.com.au